



WF 926-AUT

WF 926 SNB

Global[®] WF 920 (AUT) Series - Walking foot machines

TECHNICAL SPECIFICATIONS

Machine speed*
up to 2000 spm
Oiling system
fully automatic
Number of needles
1 or 2
Feed type
needle feed
walking foot
Presser foot lift
by hand 8 mm
by knee 15 mm
Needle gauge 926 (AUT)
standard 8 mm
other gauges available
Stitch length
up to 9 mm
Needle bar stroke
36 mm
Needle type
135x17
Stitch type
301

WF 925 - Single needle, needle feed, walking foot machine with large vertical axis hook.
WF 925 AUT - Same as above, but with thread trimmer and automatic back tack (electric).
WF 926 - Double needle, needle feed, walking foot machine with large vertical axis hook. Standard needle gauge 8 mm.
WF 926 AUT - Same as above, but with thread trimmer and automatic back tack (electric).
WF 926 SNB - Same as WF 926, but with disengageable needle bars.
WF 926 SNB-AUT - Same as above, but with electric thread trimmer and automatic back tack.

MÁQUINAS TRIPLE ARRASTRE

WF 925 - Máquina de una aguja triple arrastre, con garfio grande sobre eje vertical.
WF 925 AUT - Las mismas características que la WF 925, pero con corta-hilos y remate eléctrico.
WF 926 - Máquina de dos agujas triple arrastre, con garfio grande sobre eje vertical. Distancia entre agujas estándar 8 mm.
WF 926 AUT - Las mismas características que la WF 926, pero con corta-hilos y remate eléctrico.
WF 926 SNB - La misma que la WF 926, pero con agujas desembragable.
WF 926 SNB-AUT - La misma que la anterior, pero con corta-hilos y remate eléctrico.

DREIFACHTRANSPORTMASCHINEN

WF 925 - Einnadel-, Steppstichmaschine mit Unter-, Nadel- und alternierendem Obertransport und großem Vertikalgreifer.
WF 925 AUT - gleich wie oben, jedoch mit Fadenabschneider und Verriegelungsautomatik (elektrisch).
WF 926 - Zweinadel-, Steppstichmaschine mit Unter-, Nadel- und alternierendem Obertransport und großem Vertikalgreifer. Standard Nadelabstand ist 8 mm.
WF 926 AUT - gleich wie oben, jedoch mit Fadenabschneider und Verriegelungsautomatik (elektrisch).
WF 926 SNB - Baugleich mit WF 926, jedoch mit hochstellbaren Nadelstangen ausgestattet.
WF 926 SNB-AUT - Baugleich mit WF 926 SNB, jedoch mit Fadenabschneider und Verriegelungsautomatik.












MACHINE TRIPLE ENTRAÎNEMENT

WF 925 - Machine plate 1 aiguille, triple entraînement avec crochet de grande capacité sur axe vertical.
WF 925 AUT - Identique à la version ci-dessus avec en plus, coupe fil et arrêts automatiques (électromagnétique).
WF 926 - Machine plate 2 aiguilles, triple entraînement crochets de grandes capacités sur axes verticaux. Écartement standard 8 mm.
WF 926 AUT - Identique à la version ci-dessus avec en plus, coupe fil et arrêts automatiques (électromagnétique).
WF 926 SNB - identique à la WF 926 avec en plus les aiguilles escamotables.
WF 926 SNB-AUT - identique à la WF 926 SNB avec en plus coupe-fil et arrêts automatiques.

WF 920 (AUT) series

Single / Double needle, needle feed, walking foot machines, with or without thread trimmer and automatic back tack (all electric). Machine is designed to sew leather, safety belts, tents and car seats. (automatic lubrication). All machines are equipped with safety clutch device.

Specifications

 model	WF 925	WF 925 AUT	WF 926 WF 926 SNB	WF 926 AUT WF 926 SNB AUT
 number of needles	1	1	2	2
 Stitch length mm	9	9	9	9
 presser foot lift by hand (mm) by knee (mm)	8 15	8 15	8 15	8 15
 needle system	135x17	135x17	135x17	135x17
 space to right of needle (mm)	240	240	240	240
 max speed spm*	2000	2000	2000	2000
 manual split needle bar	—	•	—	•
 hooks	large	large	large	large
 electric presser foot lift	—	option	—	option
 machine bed plate mm	518	518	518	518



Thread trimming device and large hooks.



Solenoids for automatic trimming and back tack

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:
 1 machine model
 2 part numbers