



WF-976 - 2 needle cylinder arm

WF 975-LH

WF 976



WF 975-LH - Cylinder arm with large hook

Global® WF 970 Series - Cylinder arm walking foot machines

TECHNICAL SPECIFICATIONS

Machine speed*
up to 2000 spm

Stitch length
up to 6 mm

Needle bar stroke
33 mm

Feed type
needle feed
walking foot

Presser foot lift
by hand 8 mm
by knee 14 mm

Oiling system
manual

Hook type
WF 975 = standard
WF 975 LH = large

Needle type
135x17

Stitch type
301

WF 975 – Single needle cylinder arm machine with needle feed and walking foot. This machine is equipped with standard vertical axis hook.
WF 975 LH – Same as above, but with large vertical axis hook and adjustable inside presser foot from 2 - 5 mm.
WF 976 – Double needle cylinder arm machine with needle feed and walking foot. This machine is equipped with large vertical axis hook. Standard needle gauge 8 mm.

MÁQUINAS DE BRAZO CILÍNDRICO, TRIPLE ARRASTRE

WF 975 – Máquina de una aguja, brazo cilíndrico con arrastre por aguja, pata y dientes. Equipada con garfio normal sobre eje vertical.
WF 975 LH – Las mismas características que la WF 975, pero equipada con garfio grande sobre eje vertical y con la pata interior ajustable de 2 a 5 mm.
WF 976 – Máquina de dos agujas, brazo cilíndrico con arrastre por aguja, pata y dientes. Equipada con garfio grande sobre eje vertical. Distancia entre agujas estándar 8 mm.

ZYLINDERARM, DREIFACHTRANSPORTMASCHINEN

WF 975 – Einnadel Zylinderarm- Steppstichmaschine mit Unter-, Nadel- und alternierendem Obertransport. Die Maschine ist ausgestattet mit normalem Vertikalgreifer.
WF 975 LH – gleich wie oben, jedoch mit großem Vertikalgreifer und verstellbarem inneren Presserfuß von 2 - 5 mm.
WF 976 – Zweinadel Zylinderarm-Steppstichmaschine mit Unter-, Nadel- und alternierendem Obertransport. Die Maschine ist ausgestattet mit grossem Vertikalgreifer. Standard Nadelabstand 8 mm.

MACHINE CANON TRIPLE ENTRAÎNEMENT

WF 975 – Machine canon 1 aiguille, triple entraînement. Crochet standard sur axe vertical.
WF 975 LH – Identique à la version ci-dessus mais avec crochet de grande capacité et pied intérieur réglable de 2 à 5 mm.
WF 976 – Machine canon 2 aiguilles, triple entraînement avec crochets grandes capacités sur axes verticaux. Écartement d'aiguilles standard de 8 mm.

* Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:
1 machine model
2 part numbers