



FB 2603 UTC

Global[®] FB 2600 UTC Series - Flatbed coverstitch machines

TECHNICAL SPECIFICATIONS

Machine speed*

6000 spm

Stitch type

602 or 605

Number of needles

2 or 3

Needle gauges

4.8 - 5.6 - 6.4 mm

Feed type

differential feed

Differential feed ratio

1:0.3 - 1:2.9

Stitch length

min. 1.4

max. 3.6

Presser foot lift

up to 7 mm

Needle type

UY 128 GAS

Bed type

flatbed

FB 2602 / 2603 UTC - High speed top and bottom cover chainstitch flatbed machines, fully automatic lubrication and differential feed. Equipped with a lower and upper thread trimmer and presser foot lift (all pneumatic).

MÁQUINAS RECUBRIDORAS

FB 2602 / 2603 UTC - Alta velocidad, máquinas recubridoras superior e inferior de base plana. Lubricación completamente automática y arrastre diferencial. Equipada con corta-hilos para el hilo superior e inferior y alza-prensatejas (todo neumático).

ÜBERDECKNAHTMASCHINEN

FB 2603 / 2603 UTC - Hochleistungs- Ober- und Unterüberdecknaht-Flachbett Maschinen. Vollautomatisch geschmiert und Differentialtransport. Ausgerüstet mit einem Ober- und Unterfadenabschneider sowie Drückerfußblüftung (alle pneumatisch).

MACHINE POINT DE RECOUVREMENT BASE PLANE

FB 2602 / 2603 UTC - Machine point de chaînette à base plane à grande vitesse. Recouvrement inférieur et supérieur. Lubrification automatique et griffe différentielle. Equipée avec coupe-fils inférieur et supérieur et relevage du pied presseur (tout pneumatique).

Global FB 2600 UTC Series

The Global FB 2600 UTC Series are high quality 2 or 3 needle flatbed machines with top and bottom cover stitch and improved differential feed mechanism.

These machines are equipped with a lower and upper thread trimmer and presser foot lift (all pneumatic).



Pneumatic thread trimmer and presser foot lift



Upper threadtrimmer

Some features of the Global® FB 2600

- swing-up type looper for easy threading
- fully automatic lubrication
- high quality precision parts
- interchangeable oil-filter
- high speed: up to 6000 spm
- vibration free

Specifications

model	number of needles	number of threads	needle distance			outside stitch length mm	differential feed ratio mm	presser foot lift	needle system	max. sewing speed*
			4.8 mm	5.6 mm	6.4 mm					
FB 2602 UTC	2	4	●	—	—	1.4 - 3.6	1:03 - 1:2.9	7	UY128GAS	6000
FB 2603 UTC	3	5	—	●	—	1.4 - 3.6	1:03 - 1:2.9	7	UY128GAS	6000
FB 2603 UTC	3	5	—	—	●	1.4 - 3.6	1:03 - 1:2.9	7	UY128GAS	6000

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:
 1 machine model
 2 part numbers