



Global® BT 1850 Series - Automatic bartack machines

TECHNICAL SPECIFICATIONS

Machine speed*
up to 2300 spm
Stitch type
301
Number of stitches
BT 1850-28: 28
BT 1850-42: 42
Hook type
oscilating hook
Bartacking width
1.5 - 3 mm
Presser foot lift
max. 16 mm
Needle type
134R

BT 1850 series - These machines are available in 28 or 42 stitches and are equipped with a trimming device and are very suitable to sew on jeans and workwear etc. Semi automatic lubrication. Max. sewing speed up to 2300 spm.

MÁQUINAS DE PRESILLAS SEMI AUTOMÁTICA

BT 1850 series - Estas máquinas de presillas se suministran en 28 y 42 puntadas, llevan un mecanismo de corta-hilos, apto para coser jeans y prendas de trabajo etc. Lubricación semi-automática. Velocidad máxima 2.300 p.p.m.

SEMI AUTOMATISCHE RIEGELMASCHINEN

BT 1850 Serien - Mechanische Doppelsteppstich Riegelmaschine. Diese Maschinen sind erhältlich mit 28 oder 42 Stichen. Sie ist ausgestattet mit einem Fadenabschneider. Halbautomatische Schmierung. Maximale Nähgeschwindigkeit bis 2300 Stiche pro Minute.

MACHINE POINT D'ARRÊT SEMI-AUTOMATIQUE

BT 1850 Série - La machine est livrable en 28 ou 42 points et est équipée d'un coupe de fil automatique. Recommandée pour jeans et vêtements de travail. Lubrification semi-automatique. Vitesse maxi 2300 p/m.

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- 1 machine model
- 2 part numbers