



Global[®] EM Series - Chainstitch embroidery machine

TECHNICAL SPECIFICATIONS

Machine speed*
800 spm

Stitch type
101

Number of needles
1

Stitch length
EM - 530 = 3.5 mm
EM - 550 = 3.5 mm
EM - 570 = 4.5 mm

Needle bar stroke
14 mm

Feed
universal feed movement

Needle type
137 x 1
137 x 1 sm moss stitch

EM 530 – Chainstitch embroidery machine for medium materials, also available for moss stitch.

EM 550 – Same as above, but also suitable for tape attaching.

EM 570 – Same as above, but with a retarding device with adjustable gear system for changing from plain chainstitch to other types of stitches without removing work or rethreading the machine. Also suitable for braiding stitch and ray stitch.

MÁQUINAS DE CADENETA PARA BORDADO

EM 530 – Máquina de cadeneta para bordado para trabajos con materiales medio pesados. Adecuada para puntada en cadena.

EM 550 – La misma que la EM 530, pero adecuada para aherir cintas.

EM 570 – La misma que la EM 550, pero con un dispositivo de retraso con un sistema de cambio de velocidad ajustable para cambiar de puntada en cadena a otros tipos de puntadas sin tener que quitar el trabajo o volver a enhebrar la máquina. También es adecuada para entrelazar y rayar puntadas.

KURBELSTICHMASCHINEN

EM 530 – Einfache Kurbelstichmaschine für mittelschweren Materialien. Zur Herstellung von Moosstichen.

EM 550 – Baugleich mit EM 530, jedoch geeignet für Band- und Schnurstich.

EM 570 – Baugleich mit EM 550, jedoch zusätzlich ist diese Maschine mit einer Schalteinheit ausgestattet. Diese Maschine ist zur Herstellung von "braiding"- und "ray"-Stich.

MACHINES POINT DE CHAÎNETTE

EM 530 – Machine point de chaînette decorative. Machine idéale pour le travail à plat sur tissus moyens. Recommandée pour point mousse.

EM 550 – Identique au modèle EM 530, mais aussi destine pour la fixation de bande.

EM 570 – Identique au modèle EM 550, mais avec un mécanisme retard comportant un système d'engrenage réglable pour passer de point de chaînette à d'autres types de point sans retirer le travail ou renfiler la machine. Egalement recommandée pour point de tresse et point rayon.

* Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL[®] Selection is brought to you by:

GLOBAL[®] is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- 1 machine model
2 part numbers